



ALBATOUL

TRADING EST.

Quality & Uniqueness Integrated

Presents



Sizes & Fire Ratings for Fire Door Assemblies

Configurations, Fire Labels, and Maximum Sizes

	Non Label	20 min	B & C	A	Temp Rise B	Temp Rise A
20 Gauge Single	4' 2-3/16" x 10'	4' 2-3/16" x 10'	4' 2-3/16" x 9'	4' x 8'	4' to 4' 2-3/16" x 8'	N/A
20 Gauge PR & DE	8' 4-3/8" x 10'	8' 4-3/8" x 10'	8' 4-3/8" x 9'	8' x 8'	8' to 8' 4-3/8" x 8'	N/A
18 Gauge Single	4' x 9'	4' x 9'	4' x 9'	4' x 8'	4' x 9'	4' x 8'
18 Gauge PR & DE	8' x 9'	8' x 9'	8' x 9'	8' x 8'	8' x 9'	8' x 8'
16 Gauge Single	4' x 8'	4' x 8'	4' x 8'	4' x 8'	N/A	N/A
16 Gauge PR & DE	8' x 8'	8' x 8'	8' x 8'	8' x 8'	N/A	N/A
Solid Wood Core	4' x 9'	4' x 9'	N/A	N/A	N/A	N/A
Solid Wood Core PR & DE	8' x 9'	8' x 9'	N/A	N/A	N/A	N/A

A Label - 3 hours B Label - 1 1/2 hours C Label - 3/4 hour

Total Door provides “Smoke and Draft” labels on all positive pressure doors at no additional charge.

- FRP available on non-labeled doors only.
- Steel doors are available in all labels and most finishes except FRP.
- Solid wood core doors are available in 20 min label only with wood and HPL finish.
- Removable mullions are only available on non-labeled doors up to 10’ steel; 9’ wood core.
- Leaf sizes from 12” up to 4’ 2-3/16” x 10’ 0”.
- 8’ 4-3/8” wide pairs for a true 8’ 0” clear opening.



Strength, Safety, and Security

We carry labels for positive and negative pressure, 20 minute, 45 minute, 1-1/2 hour, 3 hour and temperature rise ratings. Testing for fire door assemblies is in compliance with ASTM E152, UL 10C, NFPA 252, and UBC standard 7-2 (1997) parts I & II and Canadian standard CAN4- S104-M80. IBC. Total Doors are ADA compliant and meet all local fire codes. They can be ordered in 1/16” increments to meet your application.

Additional Ratings

- Storm Sentry™ has been successfully tested by Certified Testing Laboratories and has received a Miami-Dode Notice of Acceptance (NOA). Available in in-swing and out-swing singles and pairs without the addition of unsightly hardware. 65 psf with glazing, 70 psf and 80 psf pressure ratings to 6' x 7' 2" pairs.
- VLR Blast 180 psf; singles and pairs up to 6'0" x 7'2"

**For more information regarding the Total
Door, contact your local distributor:**

Al Batoul Trading Est.
62 Wadi Watoub St.
P.O.Box 14400, Jeddah 21424
Kingdom of Saudi Arabia
T: +966 2 6557766 / 6557474
F: +966 2 6541157

www.AlbatoulGroup.com