

- **C-channel designation:**
North & South America = C8 x 11.5 [C200 x 17]
Europe = C200 x 75
Asia = C200 x 80

(this includes loaded deflection).

- * POWER MUST BE AVAILABLE AT TIME OF INSTALLATION

ELECTRICAL CONTRACTOR.

- WQI.

- ceiling is suspended ceiling tiles.

- otherwise.

KEY SWITCH CONTROL
CEILING SUPPORT & HANGER
CEILING ACCESS PANEL



PANEL

TYPICAL SKYFOLD WALL



24'-0" min to 36'-0" max [7315 min to 10973 max]

Micro drive unit

PLAN & MECHANICAL DETAILS

S1419

SCALE: 1/2" = 1'-0"



S1419 | SCALE: 1 1/2" = 1'-0"

SCALE: 1 1/2" = 1'-0"

NOTES TO G.C.

- Give special attention to:
 - Any obstructions to ceiling pockets & cables (i.e. ducts, sprinkler pipes, drain pipes, electrical conduits, etc.).
 - Tolerances of fixed walls & finished floor.
 - Removable ceiling tile for top of pocket.

2. Acoustic performance:

Skyfold Classic

North America: STC: 51 as per ASTM E90

Europe: Rw: 51 as per ISO 140-3, Part 3 & ISO 717-1:2

Skyfold Classic Elite

North America: STC: 57 as per ASTM E90

Europe: Rw: 56 as per ISO 140-3, Part 3 & ISO 717-1:2

Skyfold Classic NR

North America: STC: 50 as per ASTM E90

NR C: 0.65 as per C-423

Europe: Rw: 49 as per ISO 140-3, Part 3 & ISO 717-1:2

SAC: 0.65 as per ISO 354.

3. Panel finish: XXXXXXXXXXXXXXXXXXXXXXXXXX.

- Skyfold requires two 24" x 24" [610 x 610] (minimum) access panels in acoustic ceiling directly beside motor for installation & maintenance of system. Not required if finished ceiling is suspended ceiling tiles.

- Drive unit to be installed prior to construction of acoustic barrier & pocket. All pocket construction (gypsum, suspended ceiling tile, framing, etc.) is by others.

- The floor underneath the wall along its axis must be flat to within $\frac{1}{4}$ " [6] over the entire length of the wall. A peak to valley undulation of $\pm \frac{1}{4}$ " [6] must not be closer together than 24" [610]. A peak to valley undulation of $\pm \frac{3}{8}$ " [3] must not be closer together than 12" [305].

- Do not scale from this drawing. All dimensions must be verified on site.

- Dimensions in [] are in millimeters (mm) unless noted otherwise.

**C-channel designation:

North & South America = C8 x 11.5 [C200 x 17]
Europe = C200 x 75
Asia = C200 x 80

NOTE:
SEE DRAWINGS R811737 & R811738 FOR 1110" MINIMUM TO 17'-0" MAXIMUM (3605 MINIMUM TO 5180 MAXIMUM) LONG WALL CONDITIONS.
SEE DRAWINGS R811826 & R811827 FOR 17'-0" MINIMUM TO 24'-0" MAXIMUM (5180 MINIMUM TO 7315 MAXIMUM) LONG WALL CONDITIONS.

THIS DRAWING IS INTENDED AS A GUIDE. IN ALL CASES SKYFOLD SHOP DRAWINGS SPECIFIC TO EACH PROJECT ARE REQUIRED FOR FINAL BUILD-TO-DIMENSIONS.

Architect Skyfold Detailing


Project	
---------	--

TYPICAL SKYFOLD WALL

24'-0" min to 36'-0" max [7315 min to 10973 max]
x 9'-0" max [2745 max] B.O. Pocket
Micro drive unit


PANEL & POCKET DETAILS

DATE	APPROVED BY	DATE
SKYFOLD PROJECT NO.	SCALE	SHEET NO.
DRAWING NO.	AS NOTED	2 OF 2
S1420		5




C ELEVATION - WALL DOWN

S1419 | SCALE: 3/8" = 1'-0"




3 POCKET DETAIL

S1420 | SCALE: 1/2" = 1'-0"




2 END SEAL DETAIL

S1419 | SCALE: 1/2" = 1'-0"



D SECTION - WALL DOWN

S1419 | SCALE: 1/2" = 1'-0"



4 FLOOR SEAL DETAIL

S1420 | SCALE: 1/2" = 1'-0"