

DIMENSIONS FOR STANDARD DRIVE SYSTEM PANELS ≤ 673mm

25mm has been added to the beam height for European/Asian C-Channels.
Beam heights and hanger adjustments on Metric charts differ from Imperial charts for this reason.

FINISHED CEILING "A"	BEAM HEIGHT "B"	ACOUSTIC BARRIER "C"	POCKET DEPTH "D"	POCKET WIDTH "E"	PANEL HEIGHT "F"	NUMBER OF PANELS HIGH	WALL THICKNESS	MAX PANEL LENGTH ALL ZENITH MODELS
2150	2855	2525	380	1455	603	4 Panels High	300	3655
2200	2895	2570	370	1475	614			
2250	2955	2630	380	1505	629			
2300	3005	2680	380	1530	641			
2350	3055	2730	380	1555	654			
2400	3105	2780	380	1580	667			
2440	3130	2805	365	1595	673			
2450	3275	2930	505	1385	560	5 Panels High	3655	
2500	3325	2980	505	1405	570			
2550	3370	3025	500	1420	579			
2600	3420	3075	500	1440	589			
2650	3465	3120	495	1460	598			
2700	3515	3170	495	1480	608			
2750	3570	3225	500	1505	619			
2800	3615	3270	495	1520	629			
2850	3670	3325	505	1545	640			
2900	3720	3375	500	1560	649			
2950	3770	3425	500	1580	659			
3000	3825	3480	505	1605	665			
3050	3860	3520	495	1620	673			
3075	3915	3590	515	1395	575	6 Panels High	3655	
3200	4045	3720	520	1440	597			
3350	4200	3875	525	1490	622			
3500	4350	4025	525	1545	648			
3650	4505	4180	530	1595	673			
3660	4505	4180	520	1595	673			

* Beam heights indicated may vary with wall size and motor size.

This table is not for construction purposes. Refer to shop drawings for final build to dimensions.